BIO Web of Conferences **138**, 02007 (2024) https://doi.org/10.1051/bioconf/202413802007
AQUACULTURE 2024

Experiments on pressing elastic-viscous products

Gayrat Bahadirov[1], *Ayder* Nabiev[1*], and *Gerasim* Tsoy[1]

[1]Institute of Mechanics and Seismic Stability of Structures named after M.T.Urazbaev, Uzbekistan Academy of Sciences, Tashkent, 100125, Uzbekistan

Abstract. The effect of various factors on the amount of fluid removed in the technological process of squeezing multilayered raw hides by pressing between plates is experimentally studied in the article. The influence of various factors on the pressing process was determined (for example, the installation of moisture-wicking cloth between the layers of raw hides) and their patterns were established. Results were obtained to determine the effect of moisture-wicking cloth on the efficiency of the process of excess fluid extraction from wet raw hides with the pressure on leather products clamped between the lower and upper plates from 11 to 18 kN/cm^2. The installation of fibrous cloth of the BM brand increases the uniformity of fluid removal over the topographic sections of the raw hide, which reduces the storing time after squeezing moisture. The installation of a porous fibrous cloth of BM type between the layers of raw hides eliminates the difficulty of separating the layers of the raw hide. A new method for squeezing out excess fluid from wet raw hides using moisture-wicking cloth by pressing is proposed instead of using metal gratings.

1 Introduction

It is known that the purpose of post-tanning operations and processes is to prepare the hide for drying and finishing [1, 2]. These include soaking, washing, pressing, shaving, sorting for the intended purpose, neutralization, dyeing, and fat-liquoring for chrome leather and Russian leather (yuft). The squeezing of leather of any sort is conducted after washing. Stiff skins are pressed on hydraulic presses and contain 45–50% of fluid. Chrome leather, pressed on roller presses, retains fluid up to 58–62%.

The process of squeezing fluid from wet raw hides by pressing is an important technological operation in the production of leather.

Further mechanical operations and the quality of processing depend on the moisture content after the mechanical extraction of fluid by pressing. Therefore, it is necessary to study and analyze the existing mechanical devices for removing fluid from raw hides.

In the production of leather, in addition to roller squeezing machines, centrifuges, presses for squeezing wet hides and skins are successfully used. For example, there is a hydraulic press POMSH [2] for squeezing fluid from hides, which consists of three zones, in the first zone loading is carried out through a funnel, in the second zone, fluid is

*Correspondingauthor: a.nabiev@mail.ru

squeezed out by pressing, in the third zone, the skins are unloaded. The productivity of the press is determined by the size of the press cylinder and the pressing time in the second zone, which is approximately 15 minutes.

Advantages of this press. The introduction of hydraulic presses POMSH instead of centrifuges increases labor productivity and unloading of the finished skin from 1m2, reduces worker's physical costs, and improves working conditions.

An analysis of the operation of this machine showed that the disadvantage of this press is the impossibility of squeezing fluid from heavy weight wet skins; there appear many folds and creases when squeezing sheepskins, fur skins and other small hides, the elimination of which requires additional lengthening and flattening operations.

The P-902 hydraulic press [2] is used to remove fluid from stiff leathers and yuft; it contains an upper traverse with a wooden shield on four columns, which, in turn, is connected to the base, a hydraulic cylinder in the floor recess, a hydraulic drive and squeeze control system, a cart with a wooden shield, a stove and a stack of wet skins. An analysis of the press P-902 operation showed that its disadvantages are low productivity, non-uniform removal of fluid, and wrinkling at the skin fold, due to its very strong squeezing by the press plate.

To eliminate the above shortcomings in wet leather pressing devices and improve the design of these devices, the authors developed two options of a device for squeezing fluid from a wet raw hide by pressing.

The first option. When laying the skins in a kink on the plate of the cart of this device [3], a moisture-wicking cloth is placed between the skins and inside the kink, preferably made of fibrous felt materials. Laying of porous metal-ceramic materials between the skins and inside the kink of the skins and a combination of fibrous felt materials with porous cermets materials are also possible.

Plates on the traverse and on the bottom of the cart are made of porous metal-ceramic material. To intensify the removal of fluid by pressing, the surfaces of ceramic-metal materials in contact with the skin on the traverse and cart are made convex upwards, and the metal-ceramic plates laid between the skins and inside the kink are made curved or convex, so that the outer and inner surfaces are equidistant to the surfaces on the plate of the traverse and cart.

In the proposed device, a moisture-wicking fibrous cloth is installed between the skins and inside the kink. Due to this, under the pressing force, the liquid flowing out of the skin penetrates into the insides of the moisture-wicking cloth, from where it flows down the ends.

The installation of moisture-wicking fibrous cloth ensures uniform distribution of the pressure force on the skin surface, since the skin differs in thickness and density in different topographic sections.

The second option. To solve this problem, in the proposed design of a device for pressing wet leather products, moisture-wicking cloth and wet raw hides are placed layer by layer on the lower press plate [4].

When using the proposed device for squeezing fluid from wet raw hides by pressing, the quality of squeezing fluid and the yield of leather over the area are improved and the quality of subsequent technological processes increases.

A multi-tiered hydraulic press for pressing and drying of, for example, felt circles is known; it includes hollow gasket plates heated by steam or electricity. The described press for squeezing and drying differs from the above presses in that it uses a known device for drying by passing an alternating electric current through the material to be dried. This device is made in the form of conductive tires mounted on the side of the press, connected to the clamps of the gasket plates for supplying electric current to them; the upper planes of the plates are perforated.

At the end of pressing and squeezing, limited by stops, the current is supplied to the gasket plates. An electric current passing through felt circles heats them up and dries them. By the end of drying, the current drops to a minimum and automatically turns off. After that, the working plate is taken down; felt circles are removed from the press and dried in ordinary dryers.

As a result of the analysis of the factors influencing the process of fluid removing from the raw hide on presses, new devices for its extraction, are proposed (certified as inventions).

2 Material and method of research

During the experimental study, it is necessary to conduct the following program of work:

to investigate the influence of the installation of a moisture-wicking cloth of BM brand between the layers of raw hides and to determine their dependencies;

to reveal the effect of a BM cloth on the amount of fluid removed from a wet raw hide by pressing and to determine their dependencies.

Methodology for conducting experimental studies. In the experimental study, it was necessary to establish patterns of influence of various factors on the amount of fluid removed under pressing. Since the manufacture of a life-size experimental stand is expensive, the process of squeezing fluid was simulated on a smaller stand. When modeling the process of pressing fluid from a raw hide on a stand, the question arises of reducing the width of samples of a raw hide, which would lead to material savings during the experiment. Therefore, it is necessary to select samples of raw hides of different widths, feed them between the pressing plates and compare the change in the amount of squeezed fluid in the samples of raw hides of different widths [4–6].

For an experimental study of the influence of various factors on the process of squeezing fluid from a wet raw hide by pressing, it was necessary to select its parameters, develop drawings, and make an experimental stand.

The experiments were conducted on the stand of the pressing machine, where the raw hides were mounted; the springs were compressed by tightening the nuts to the desired clamping pressure. A group of samples of the raw hide was taken and 5 or 10 layers were installed on the plates. The samples were weighed before and after pressing on XES-1000 (ISO-9001) scales. Then the relative amount of fluid removed from the samples of raw hides was determined by the following formula [7–9]:

$$W = \frac{A-B}{A}100\ ,\ \% \tag{1}$$

where W – amount of fluid removed from the samples of raw hides; A – are the weights of samples before after pressing; B – are the weights of samples after pressing.

The experiment was conducted with various combinations of a raw hide with BM cloth [10–12].

To study the natural phenomena of the process by modeling, i.e. to study of similar phenomena on a smaller scale model, theories of similarity and dimensions were developed.

Samples for pressing raw hides cut from splitted bovine skins of heavy weight were taken according to state standards ISO-2588-85 by formula $n = 0.2\sqrt{x}$, where x is the number of raw hides in the batch, n is the number of raw hides for the experiment [13–17].

After chrome tanning and splitting, x=2500 raw hides were taken; so, n=10. From these 10 samples of raw hide strips were cut across the spinal line with a cutter 5×5 cm, 5×23 cm in size, 10 pieces per batch [18–22].

3 Results

As a result of the experiments, the initial weight of wet samples of raw hides, and their final weight after pressing on the experimental stand, were measured on laboratory scales.

Figure 1 shows an experimental stand for pressing wet raw hides, and Figure 2 shows the same stand for pressing wet raw hides in combination with a cloth of BM brand by pressing. The parameters of this experimental stand are: on plate 1, four guide cylindrical posts 2 are fixed, on which supports 3, 4 are installed, on which plates 5 and 6 are fixed.

The upper plate 5 is pressed against the lower plate 6 by four springs 7 mounted on the guide posts 2 and resting with one end on supports 8 and the other end on nuts 9. The pressure on the shafts is realized by compressing springs 8 from below with jack 10 installed on plate 1 or by tightening the springs with nuts 11 (not shown in Figures 1 and 2). The springs are pre-calibrated. Additionally, load 12 was set (not shown in Figures 1 and 2).



Fig. 1. Experimental stand for squeezing wet raw hides by pressing [Compiled by the authors].

Table 1. The results of measuring the weight of wet raw hides before and after pressing.

№	y_1, gr		y_2, gr		y_3, gr		y_4, gr		y_5, gr	
	y_{1in}	y_{1af}	y_{2in}	y_{2af}	y_{3in}	y_{3af}	y_{4in}	y_{4af}	y_{5in}	y_{5af}
1	16.0	9.5	19.0	14.0	17.0	10.5	19.0	14.0	17.5	13.0
2	13.5	8.5	16.5	12.0	14.0	9.0	18.5	14.5	17.5	13.0
3	17.5	13.0	15.5	11.0	17.5	13.0	17.5	13.0	18.5	13.5
4	15.5	12.0	15.5	11.0	16.0	11.5	16.5	12.5	18.0	13.0
5	15.5	11.5	18.5	13.5	16.0	11.5	19.0	14.0	17.5	12.5
6	17.5	13.5	17.0	10.5	18.5	13.5	17.0	13.0	18.0	12.5
7	17.5	13.5	17.0	10.5	18.5	13.5	17.0	13.0	18.0	12.5
8	18.5	14.0	17.5	12.0	18.0	14.0	17.5	12.5	17.0	12.0
9	15.5	9.5	16.0	10.5	16.0	11.0	16.0	11.5	16.0	12.0
10	17.0	12.0	16.0	11.0	19.5	14.5	16.0	12.0	18.5	13.5

[Compiled by the authors]
y_{in} is the initial weight of a sample of a wet raw hide.
y_{af} is the weight of a raw hide sample after squeezing out excess fluid.

Table 2. The results of measuring the weight of wet raw hides in combination with moisture-wicking cloths (cloth of BM brand) before and after pressing.

№	y_1, gr		y_2, gr		y_3, gr		y_4, gr		y_5, gr	
	y_{1in}	y_{1af}	y_{2in}	y_{2af}	y_{3in}	y_{3af}	y_{4in}	y_{4af}	y_{5in}	y_{5af}
1	15.5	9.0	17.0	11.0	16.5	11.5	18.0	13.0	19.0	13.0
2	13.5	8.5	19.0	13.5	16.0	11.5	19.5	14.0	19.0	14.5
3	17.5	12.0	19.5	15.0	17.0	11.0	18.0	11.0	18.5	13.5
4	15.5	10.5	17.5	13.0	19.0	13.5	19.0	13.0	16.0	12.0
5	16.0	10.5	16.5	12.0	18.0	13.5	18.0	12.5	15.0	10.5
6	18.0	13.0	18.5	14.5	17.0	10.5	20.0	10.5	16.0	10.0
7	18.5	14.0	17.5	13.5	18.5	12.0	18.5	11.5	17.0	12.5
8	17.5	13.5	17.0	12.5	17.5	11.0	17.5	12.0	15.5	11.0
9	14.5	8.5	16.5	12.0	16.0	10.5	17.5	10.5	17.5	11.5
10	18.5	14.5	18.5	12.5	17.5	11.5	19.0	12.5	16.5	11.5

[Compiled by the authors]

In Tables 1 and 2, the pressure force is 18 kN/cm^2, and the dimensions of the samples of raw hides are 5 × 5 cm.

Figure 2 shows an experimental stand manufactured according to the patent of the Republic of Uzbekistan No. FAP 00732 in the mechanical workshop of the Institute of Mechanics and Seismic Stability of Structures of the Academy of Sciences of the Republic of Uzbekistan [23–28].



Fig. 2. Experimental stand for squeezing wet raw hides in combination with BM cloth by pressing [Compiled by the authors].

The mechanism of action of a full-scale system, that is, the process of removing fluid, is not well understood, the equation describing this phenomenon is unknown, and full-size modeling is not possible, especially since the fluid flow through a porous roller has not been studied either. Full-size modeling of the process of fluid removal from the raw hide by roller squeezing machines is impossible, therefore, a partial modeling analysis was conducted. Let us consider, for example, the length and width of the plates of the dimensions of the pressed plates. If these plates are modeled on a bench, then their dimensions can be significantly reduced [29–33].

Figure 3 shows a dependence graph of fluid ΔW removed from wet raw hides (with and without cloth) on pressing time.



Fig. 3. Change in the amount of fluid ΔW removed depending on time under a pressure of 11 kN/cm^2 [Compiled by the authors].

The influence of the dimensions of the plates on the pressing process is studied by changing the width and length of the raw hide fed for pressing during the experiment. The pressing force of plates is simulated based on the existing squeezers. In this regard, all the simulated parameters on the experimental bench are taken as full-scale ones, except that the area of plates and the area of raw hides are taken smaller. Considering the above, the parameters of the experimental bench were: on plate 1, four guiding cylindrical posts 2 were fixed, on which supports 3 and 4 were installed, on which plates 5 and 6 were fixed (Figures 1, 2) [34–39].

The upper plate 5 is pressed against the lower plate 6 by four springs 7 mounted on the guiding posts 2 and resting with one end on supports 8 and the other end on nuts 9. The pressure on the rollers is realized by pressing springs 8 from below with jack 10 installed on plate 1 or by tightening the springs with nuts 11. The springs are pre-calibrated. Additionally, a load was fitted [40–44].

In Tables 3 and 4, the pressing force is 11 kN/cm^2. The dimensions of the skins are 5×23 cm (stacked in 2 layers in a kink). The results of measurements of the amount of fluid removed from wet samples of raw hides in various combinations are listed in Tables 3 and 4 [45–48]. Table 3. Amount of fluid squeezed from wet raw hides after pressing.

Table 3. The results of measuring the weight of wet raw hides in combination with moisture-wicking cloths (cloth of BM brand) before and after pressing.

№	Measurement results, in %					
	y_1	y_2	y_3	y_4	y_5	y_{av}
1	40.6	26.3	38.2	26.3	25.7	26.3
2	37.0	24.2	35.7	32.4	28.6	31.6
3	28.6	29.0	25.7	25.7	27.0	27.2
4	22.6	29.0	28.1	24.2	27.8	26.3
5	26.8	27.0	28.1	26.3	28.6	27.3
6	22.9	37.1	27.0	29.6	30.6	29.4
7	21.6	20.6	21.6	28.6	25.0	22.5
8	24.3	31.4	22.2	28.6	29.4	27.2
9	38.7	34.4	31.2	28.1	25.0	31.5
10	29.4	31.3	25.6	26.6	27.0	28.0

[Compiled by the authors]

RETRACTED



Fig. 4. Change in deformation of a package of ten layers of wet raw hides depending on time (raw hides dimensions: 5x23 cm) [Compiled by the authors].

Table 4. The results of measuring the weight of wet raw hides in combination with moisture-wicking cloths (cloth of BM brand) before and after pressing.

№	Measurement results, in %					
	y_1	y_2	y_3	y_4	y_5	y_{av}
1	41.9	35.3	30.3	27.8	24.8	32.0
2	37.0	28.9	28.1	28.2	23.7	29.2
3	31.4	23.1	35.3	38.9	27.0	31.1
4	35.5	25.7	28.9	31.6	25.0	29.3
5	34.4	27.3	25.0	30.6	30.0	29.5
6	27.8	21.6	38.2	47.5	37.5	34.5
7	25.0	22.9	35.1	37.8	26.5	31.5
8	22.9	25.7	37.1	31.4	29.0	29.2
9	41.1	27.3	34.4	40.0	34.3	35.4
10	21.6	32.4	34.3	34.2	30.3	30.6



Fig. 5. Change in deformation of a package of ten layers of wet raw hides depending on time (raw hides dimensions: 5x23 cm) [Compiled by the authors].

Thus, the authors have conducted experimental studies and obtained results to determine the effect of moisture-wicking cloth on the efficiency of removing excess fluid from wet raw hides with the pressure applied to wet raw hides sandwiched between the lower and upper plates equal to 11 kN/cm^2 [49, 50].

4 Discussion

The study in [2] shows the use of a moisture-wicking material made of BM cloth as the conveyors between which leather layers are placed to remove fluid; then they pass between two rotating rollers of a squeezing machine. It is effective in removing fluid from wet skin.

The studies in [3, 5, 6], including experimental ones, confirm the results obtained when squeezing fluid from wet raw hides with a moisture-wicking cloth folded in a kink on the base plate between the layers with the results of the experimental study presented in this article. The arrangement of the moisture-wicking porous, fibrous cloth of BM brand as a coating for the squeezing rollers increases the amount of fluid extracted from the hide, provides a more uniform residual moisture content after the squeezing process on a roller machine and reduces the aging time to level out the residual moisture content in all topographic sections: shoulder, belly, and butt. The experiment of multilayer simultaneous squeezing [5, 6] with the installation of a moisture-wicking cloth of LASH or BM brand between the hide layers also confirms the results obtained in this article. These are the results of an experimental study on the non-sticking of the skin layers to the moisture-wicking cloth of BM brand and an increase in the amount of fluid extraction, an increase in the uniformity of the residual moisture content in skins after their squeezing out.

The study in [9] presents the results of an experimental study of squeezing fluid out of wet raw hides by placing the moisture-wicking cloth of LASH brand folded in a kink on a sliding rod, and then wet hides are fed vertically between horizontal rollers coated with BM cloth; this study also confirms the results obtained in this article. The experimental work conducted in [10] confirms an efficiency increase in squeezing fluid out of wet leather when installing the moisture-wicking cloth of LASH brand between the layers of the skin during multilayer squeezing; these studies also confirm the results obtained in this article.

5 Conclusion

An analysis of existing presses for removing fluid from raw hides showed the following disadvantages:

a) when pressing several layers of leather at the same time, bent into a kink in two layers, the separation of each layer is difficult due to the adhesion of each layer.

b) the installation of porous fibrous material such as cloth of BM brand between the layers of raw hides eliminates the difficulty of separating the layers. It increases the amount of fluid removed and makes it possible to increase the productivity of fluid extraction by pressing.

Thus, the authors conducted experimental studies and obtained results to determine the effect of moisture-wicking cloth on the efficiency of extracting excess fluid from wet raw hides under the pressure force (from 11 to 18 kN/cm^2) applied to wet raw hides sandwiched between the lower and upper plates.

The practical significance of the study is that the experiment showed that fluid removal by pressing raw hides only, leads to the need to apply a large force to separate each layer after pressing. Besides, when pressing a package of several layers of raw hides, fluid is removed only horizontally through the gaps between their layers and through longitudinal filtration in the hide, which is not effective. By putting a moisture-wicking cloth between the skin layers, namely, a capillary porous material made of BM cloth, it is shown that they do not stick strongly; the uniformity of the residual moisture content increases due to the elasticity of the moisture-wicking material of the BM cloth and more fluid is removed under equal conditions of pressing force and pressing time. This leads to an increase in fluid extraction. The quality of fluid removal by pressing is also improved.

In the future, the installation of a porous permeable ceramic-metal plate between the layers of raw hides is effective; fluid penetrates from the skin only down to its thickness, and then, due to the low longitudinal hydraulic resistance in the porous metal-ceramic plate, it is easily removed through the longitudinal holes in the plate.

In the future, the fluid extraction from a raw hide by pressing will be experimentally investigated; it will be stretched by centrifugal force due to the rotation of the lower plate with the layers of wet raw hides and moisture-wicking fibrous cloth. This will be performed on a bench manufactured according to the patent obtained [4].

The essence of the above patent is as follows. Moisture-wicking materials and wet skins were sequentially placed on the lower press plate, making up a package. The hydraulic system is turned on and oil is supplied to the lower cavity of the hydraulic cylinder. The piston pushes the rod with the lower pressure plate up until its contact with the stop. Then the motor is turned on. The rotation is transmitted through the gearbox and the small gear to the large gear, which rotates the lower press plate. Next, we increase the velocity of rotation of the lower press plate, together with moisture-wicking materials and wet skins, to the required value. Then we gradually increase the pressing force of the lower press plate to the required value against the upper press plate. Then the lower and upper press plates with a package of moisture-wicking materials and wet skins are pressed against each other and rotate around their axes.

Centrifugal forces stretch thin, loose hide sections faster than thick, dense sections, such as butt and shoulder sections. The clamping force (pressure) of the press plates after stretching by centrifugal forces is distributed non-uniformly over the skin sections: belly, shoulder, and butt. That is, thick and dense skin sections (shoulder and butt) are subject to higher pressing force than loose and thin sections of skin. This has a beneficial effect on the process of fluid removal since it is more difficult to remove fluid from the dense skin sections (shoulder and butt) and more pressing force is needed.

Therefore, the successive application of centrifugal force with the pressing force on the plates has a beneficial effect on the process of fluid removal from wet hides. Productivity, the quality of fluid extraction and the yield area of skins increase, and at the same time, the quality of the subsequent technological processes is improved [4].

References

1. D.V.Donya, A.A.Leonov, 2008 Engineering rheology / Textbook. Kemerovo Technological Institute of Food Industry. Kemerovo.
2. Geoffrey, E.Attenburrow, 1993 The Rheology of Leather - A Review. Journal- Society of Leather Technologists and Chemists **77(4):**107-1.
3. P.P.Rymkevich, A. S. Gorshkov // News of higher educational institutions. Light industry technology. – 2022. – **V. 55**, No. 1. – P. 8-12. – DOI 10.46418/0021-3489_2022_55_01_02.
4. V. V. Golovina, P. P. Rymkevich, V. I. Vagner // News of higher educational institutions. Light industry technology. – 2022. – **V. 55**, No. 1. – P. 13-18. – DOI 10.46418/0021-3489_2022_55_01_03.
5. A.G.Ward, The mechanical properties of leather. Rheol Acta **13**, 103–112 (1974). https://doi.org/10.1007/BF01526892
6. S.L.Furashova, V.E.Gorbachik, P.I.Skokov, Using model methods to describe the stress relaxation of footwear materials // Bulletin of the Kazan Technological University. 2007. No. 6. URL: https://cyberleninka.ru/article/n/ispolzovanie-modelnyh-metodov-dlya-opisaniya-relaksatsii-napryazheniy-obuvnyh-materialov (date of access: 01/16/2024).

7. Zheng Li, Denis Paudecerf, Jiashi Yang. Acta Mechanica Solida Sinica. **Volume 22**, Issue 1, 2009. Pages 37-44. https://doi.org/10.1016/S0894-9166(09)60088-4
8. N.V.Tikhonova, I.Sh.Abdullin, L.Yu.Makhotkina, T.V.Zhukovskaya, A.R.Yusupova, Study of the deformation characteristics of a multilayer shoe upper blank material after plasma exposure // Bulletin of the Kazan Technological University. 2014. No. 2. URL: https://cyberleninka.ru/article/n/issledovanie-deformatsionnyh-harakteristik-mnogosloynogo-materiala-zagotovki-verha-obuvi-posle-plazmennogo-vozdeystviya (date of access: 01/16/2024).
9. A.T.Amanov, et al., 2019 Journal Materials. **Volume 12**, Issue 21, November (1). Basel, Switzerland. https://doi.org/10.3390/ma12213620
10. A.T.Amanov, et al., 2023 // International Journal on Advanced Science, Engineering and Information Technology, **Vol. 13** (2023) No. 1, Indonesia. P. 321-328. DOI:10.18517/ijaseit.13.1.17360
11. A.P.Filin, Applied mechanics of a deformable rigid body. Main editorial office of physical and mathematical literature of the “Nauka” publishing house, 1975. 832 p.
12. I.N.Khusanov, G.N.Tsoy, U.I.Khusanova, Method for determining the rheological parameter during the deformation of a material. //Patent for invention UZ No. IAP 05761. Publ. bulletin No. 2, 02/28/2019
13. A.G.Burmistrov, A device for determining the relaxation properties of leather and similar flexible materials RF Patent No. 2210753.. Publ. 08/20/2003, Bulletin. No. 23.
14. A.G.Burmistrov, A.V.Kocherov, D.M.Grodsky, On the accuracy of approximation of relaxation functions on the “RELAX” installation. Thematic collection of scientific works of MGUDT, 2007, pp. 262-264.
15. A.G.Burmistrov Machines and devices for the production of leather and fur / A.G. Burmistrov – M.: Kolos S, 2006. – 384 p.
16. Leather Processing & Tanning Technology Handbook 2011 NIIR Board of Consultants & Engineers// ISBN-10: 8190568590, p. 592. https://books.google.com.hk/books?id=hbKkCwAAQBAJ
17. M.Renaud, M.Rueff and A.Rocaboy, Mechanical behaviour of saturated wood under compression// Wood Sci. Technol. C 1996
18. A.G.Ward , The mechanical properties of leather Rheol. Acta.1974
19. R.J.Santos, D.L.Agostini,F.C.Cabrera, E.R.Budemberg and A.E.Job, Recycling leather waste// Preparing and studying on the microstructure, mechanical, and rheological properties of leather waste/rubber composite Polym. Compos. 2015
20. A.Amanov et al., 2023 A Study on the Pressure Mechanism Improvement of a Roller-Type Machine Working Bodies. J Materials. **16(5):**1956. Switzerland. https://doi.org/10.3390/ma16051956
21. A.T.Amanov, et al. 2021 Improvement of the Process of Mechanical Dehydration of Five-Layer Semi-finished Wet Leather Products// Text. Leather Rev. https://doi.org/10.31881/TLR.2021.27
22. A.T.Amanov, et al. 2022 Effect of Multilayer Processing of Semi-finished Leather Products// International Journal of Mechanical Engineering and Robotics Research. Vol. 11, No. 4, 2022. pp. 248-254. DOI:10.18178/ijmerr.11.4.248-254
23. G.Bahadirov, et al., 2023 Determination of rational parameters of a device for leather feeding to the machining area// Eastern-European Journal of Enterprise Technologies, 2(1 (122). Kharkiv. 62–72. https://doi.org/10.15587/1729-4061.2023.277393

24. G.A.Bahadirov, A.A.Umarov, A.M.Nabiev, G.N.Tsoy, Experimental determination of the non-homogeneity of the physical parameters of a leather semi-finished product// E3S Web of Conf. Volume 389, Ural Environmental Science Forum “Sustainable Development of Industrial Region” (UESF-2023). https://doi.org/10.1051/e3sconf/202338901028
25. G.A.Bahadirov , et al., 2023 The effect of roller pressure and feed rate on hides squeezing// E3S Web of Conf. Volume 402. International Scientific Siberian Transport Forum - TransSiberia 2023. https://doi.org/10.1051/e3sconf/202340210016
26. T.Y.Amanov, S.D.Baubekov, G.N.Tsoy, A.M.Nabiev, 2018 Device for Providing Pressure Force between Working Bodies of Roller Technological Machines// Mod - High-Tech Technol. №9 https://top-technologies.ru/ru/article/view?id=37151
27. Y.Xia, S.Wei, Y.Deng, Y.Jin, A new enriched method for extended finite element modeling of fluid flow in fractured reservoirs //Comput. Geotech.
28. S.Bandara and K.Soga, Corrigendum to Coupling of soil deformation and pore fluid flow using material point method// [Comp. Geotech., 63(1) (2015) 199-214] DOI: 10.1016/j.compgeo.2014.12.007 Comput. Geotech.
29. Y.Xiao, Z.Tang, X.Hong and S.Chen, Application of normalized SPH method to inviscid fluid flows with large deformation of free surface Comput. Fluids
30. H.Wang, Z.Tan, S.Kuang and A.Yu, Numerical modeling and analysis of particle-fluid flow and wall erosion in centrifugal slurry pumps under different solid concentrations// Powder Technol.
31. B.Shi, J.Wei and Y.Zhang, A novel experimental facility for measuring internal flow of Solid-liquid two-phase flow in a centrifugal pump by PIV //Int. J. Multiph. Flow.2017
32. G.Peng, X.Huang, L.Zhou, G.Zhou and H.Zhou, Solid-liquid two-phase flow and wear analysis in a largescale centrifugal slurry pump// Eng. Fail. Anal. 2021.
33. R.Tarodiya and A.Levy, Surface erosion due to particle-surface interactions// A review Powder Technol.2021
34. E.Onem, Quality properties of leather produced in water and supercritical fluid// (SCF) media J. CO2 Util.2018
35. G.Krishnamoorthy, S.Sadulla, P.K.Sehgal and A.B.Mandal, Green chemistry approaches to leather tanning process for making chrome-free leather by unnatural amino acids// J. Hazard. Mater.2012
36. M.AL.Sayegh, D.Rouzineau, M.Meyer, E.Cid, P.Alix, C.Dalmazzone and J.Roesler, Impact of physico-chemical properties on falling liquid films flow over flat and corrugated surfaces Int. J. Multiph. Flow.2022
37. R.Khan, R.Kumar, Z.Ma, Experimental investigations on the performance characteristics of plastic surfaces for developing low flow falling film liquid desiccant regenerators// Sol. Energy.2022
38. A.M.Nabiev, 2022 Combined extraction of liquid from wet leather semi-finished products// 7th International Conference on Industrial Engineering. Lecture Notes in Mechanical Engineering. Springer, Cham. doi:org/10.1007/978-3-030-85233-7_59
39. G.N.Tsoy, 2022 Experimental determination of the influence of fibrous material on the dehydration of wet semi finished leather product// Proceedings of the 7th International Conference on Industrial Engineering (ICIE 2021). Lecture Notes in Mechanical Engineering. Springer, Cham. https://doi.org/10.1007/978-3-030-85233-7_60

40. G.Bahadirov, et al., 2022 Study of the efficiency of squeezing moisture-saturated products// EUREKA: Physics and Engineering, 2022 (1), 86-96. https://doi.org/10.21303/2461-4262.2021.001606
41. A.T.Amanov, et al., 2021 A New Method to Wring Water-Saturated Fibrous Materials //International Journal of Mechanical Engineering and Robotics Research, Vol. 10, No. 3, pp. 151-156, March. DOI: 10.18178/ijmerr.10.3.151-156
42. G.Bahadirov, et al., 2023 Experimental dehydration of wet fibrous materials// International Scientific Conference "Construction Mechanics, Hydraulics and Water Resources Engineering" (CONMECHYDRO - 2021), Tashkent, Uzbekistan, Edited by Bazarov, D.; E3S Web of Conferences, 2021 Volume 264, id.04060 DOI: 10.1051/e3sconf/20212640406
43. A.M.Nabiev, et al., 2023 Conditions for vertical pulling of semi-finished leather products under driving rollers// E3S Web of Conf. Volume 376, International Scientific and Practical Conference "Environmental Risks and Safety in Mechanical Engineering" (ERSME-2023). https://doi.org/10.1051/e3sconf/202337601073
44. A.Umarov, A.Nabiev, K.Khusanov, A.Shernaev, Features of parameters of a pair of rolls. AIP Conf. Proc. 21 November 2023; 2821 (1): 030020. https://doi.org/10.1063/5.0159452
45. A.M.Nabiev, G.N.Tsoy, G.A.Bahadirov, Ensuring conditions for the squeezed fluid flowing from the skin along the conveyor of the technological machine // E3S Web of Conf. Volume 458, 2023; International Scientific Conference Energy Management of Municipal Facilities and Environmental Technologies (EMMFT-2023) https://doi.org/10.1051/e3sconf/202345802015
46. A.M.Nabiev, G.N.Tsoy, G.A.Bahadirov, Device for determining permeability of tanning liquid // International Journal of Modem Manufacturing Technologies ISSN 2067-3604, Vol. XV, No. 3 / 2023 https://doi.org/10.54684/ijmmt.2023.15.3.8
47. G.A.Bahadirov, et al., 2023 Equipment and technology for processing raw hides: – Monograph; – Novosibirsk: Publishing house LLC "SibAK". – 214 p.– EDN BPGDBU.
48. G.A.Bahadirov, et al., 2023 Determination of the parameters of the chain conveying device of the roller machine // Izvestiya Vysshikh Uchebnykh Zavedenii, Seriya Teknologiya Tekstil'noi Promyshlennosti № 5 (407). – p. 168-174. https://ttp.ivgpu.com/wp-content/uploads//2023/12//407_24.pdfhttps://doi.org/10.1186/s42825-019-0017-5
49. A.M.Nabiev, et al., 2024 Experimental determination of the breakaway force of working rolls when processing semi-finished products // BIO Web Conf. Volume 93. International Scientific Forestry Forum 2023: Forest Ecosystems as Global Resource of the Biosphere: Calls, Threats, Solutions (Forestry Forum 2023). https://doi.org/10.1051/bioconf/20249303007
50. S.V.Ershov, I.A.Suvorov, V.B.Kuznetsov, E.N.Nikiforova, E.N.Kalinin, No. **1 (391)** Textile Industry Technology 2021. – P. 114-119. DOI 10.47367/0021-3497_2021_1_114